





• **P-Series** blast cabinets are designed for use with: glass beads, glass grit, aluminum oxide, silicon carbide, mineral slags, or other blast media with a bulk density greater than 80 lb/ft and less than 130 lb/ft. PMB-Series and PSS-Series machines will accommodate lighter and heavier media's than mentioned above. Media type and size should be specified.

PRESSURE SERIES BLAST CABINETS



HIGH PRODUCTION

• The Mod-U-Blast[®] "P Series" Pressure Dry Blast Cabinets are engineered for maximum production (3 to 4 times faster than standard suction blasting - "S Series"). Mod-U-Blast® Pressure Cabinets are equipped with a Pneumatic Valve for optimum safety and blast media flow, direction and velocity (foot pedal operated). Pressure systems give the control needed to clean at gentle pressures (10 to 20 PSI) or aggressive cleaning as high as 110 PSI. Minimum pressure with Suction Systems is 30 to 40 PSI.

OUALITY

 All Mod-U-Blast[®] P-Series cabinets are constructed with heavy duty 14 gauge steel, external lighting system, safety glass viewing window, and overlapping positive tension doors.

• With Mod-U-Blast's exclusive modular design it becomes easy to choose the system that best suits your budget and your specific blast cleaning application. Ten (10) standard sizes available (Custom sizes available upon request). We can recommend a Mod-U-Blast® system to manage virtually any blast cleaning application.

- All systems can be easily upgraded at any date with Mod-U-Blast's adaptable production upgrade kits.
- · Perforated steel floors come standard no expanded metal.

EFFICIENCY

MEDIA RECLAIMER:

 Precision engineered and designed, the Mod-U-Blast[®] media cyclone reclaimer delivers separation of blast media, oversized foreign matter, and dust. Equipped with replaceable wear plate for reduced long term maintenance costs.

 Also available as an upgrade kit for cabinets without reclaimers (Reclaimers 900 CFM & greater are mounted on a stand)

600 CFM reclaimer pull through style illustrated. For use with Reverse Pulse **Dust Collectors**

Electrical Requirements


CFM	HORSE POWER	PHASE / AMPS REQUIRED
300	1/2 H.P.	1-Phase / 7 Amps
600	1 H.P.	1-Phase / 14 Amps
900	2 H.P.	1-Phase / 20 Amps
1200	5 H.P.	3-Phase / customer Specified

METERING / REMOTE SYSTEM:

 Mod-U-Blast[®] pressure cabinets come standard with a M-Valve metering valve for defined efficiency. This valve allows for the fine-tuning of the flow of media to the mixing point where the abrasive meets the air flow. All pressure cabinets come equipped with a auto-air valve/blow down system that is controlled by foot controlled pedal. Once foot pedal is activated, the auto-air valve opens and the blow down valve closes pressurizing the blast vessel to the pre-regulated blast pressure that will start the blast cycle. Once foot pedal is released, the process reverses and the blast vessel blows down into the rubber lined hopper of the blast cabinet.



Increase production by upgrading from standard 0.7 Cu. Ft pressure vessel to 3.5 Cu. Ft pressure vessel. *For 900 CFM reclaimers or bigger*



CONSTRUCTION

• 14 gauge one piece steel construction

 Powder Coated white interior cabinet and hammertone grey exterior for durability. Mod-U-Blast[®] uses overlapping positive tension doors with adjustable hand latch system.











 High puncture and snag resistance. Natural rubber glove with a sewn nitrile.

PNEUMATIC FOOT PEDAL



DUST COLLECTION

MULTI-BAG DRY FILTER CABINETS

 Mod-U-Blast[®] multi-bag dust filter cabinets incorporate either 15, 25, 40 or 50 (300, 600, 900 and 1200 CFM) cotton sock type filter bags which are tightly mounted into steel housings (top and bottom). Clean air is returned to the outside of the louvered panel door and dust and dirt are contained in bottom.

• Manual Shaker is used to clean dust socks at intervals. Air volume damper control is also standard on all Mod-U-Blast[®] filter cabinets. Also available as upgrade kit for machines with dust bag only. Recommended for more frequent use, high production.

• Dust is collected either in a drawer or a hopper with clean-out hatch. The hopper style is recommended and standard configuration unless there is a height restriction. If you require low-profile, the drawer style is available.





www.modublast.com

NODT

STANDARD FEATURES

LIGHTING SYSTEM

external LED lighting system features 2 - 24" tubes in cabinets that are less than 36" in depth, and a dual-fixture system with 4-24" tubes in cabinets 36'

Mod-U-Blast's

or larger in depth.



METERING / REMOTE SYSTEM



• 0.7 Cu. Ft or 1 Cu. Ft. pressure pot • Micro Valve • Auto Air Valve • Dump Valve • Safety Relief Valve



• Quick change safety glass window with replaceable protector and trim-Lok window seal.

MOISTURE SEPARATOR, REGULATOR & GUAGE CONTROL PANEL





ADDITIONAL FEATURES:

- · Perforated steel flooring
- Powder coated for durability
- Replaceable reclaim wear plate
- Adjustable air intakes for clear visibility
- · Safety door shut-offs

- High pure gum content abrasive blast hose
- Strategically rubber lined hopper
- Cabinets are 100% modular and fully upgradable
- **REVERSE PULSE CARTRIDGE DUST COLLECTION**

 Mod-U-Blast[®] reverse pulse cartridge dual collectors are available from 300 CFM to 12000 CFM. They provide optimum clean air environments for blast cabinets, booths and blast rooms. Reverse pulse collectors feature efficiency 280 pleated filter cartridges.

• Models M300-2C, M600-2C, M900-2C, M1,200-C, M3000-6C, M6000-12C, M9000-18C, M12000-24C come standard with auto-timed controls. Hopper Discharge is standard with all reverse pulse collectors.

• Low profile models also available.



600 CFM model



1200 CFM mod





TURNTABLES & TRACK SYSTEMS

Available with inside and/or outside track assembly or as set-in turntable only. Standard turntables hold up to 700 lbs, custom turntables hold up to 2000 lbs. Mod-U-Blast[®] turntable systems will increase worker convenience, comfort and productivity while decreasing glove wear, hand injuries and overall operator fatigue. Ideal for blast cleaning larger, heavier components. May be furnished for one (1) or both (2) sides of the blast cabinet. *Custom sizing available.



PIPE ROLLING CARTS



PASS THROUGH KITS

Custom pass through kits available for new or existing cabinets.



Save time and discomfort blasting pipe with Mod-U-Blast[®] pipe rolling carts.



Wear kits are available for all machine sizes. This option is recommended when harsh blast media is being used, eg: aluminum oxide. A cabinet wear kit will extend the life of any machine regardless of the media being used.

Each wear kit includes: 1/16" Natural gum draping on sides and back of cabinet, H.D. rubber lined return hose, and tungsten carbide blast nozzle.* Urea spray lining available

HEPA RETURN FILTER



Available with all reverse pulse Cartridge dust collector models. 99.99% particulate removal efficiency



H.D. DESICCANT INLINE AIR DRYERS



These single tower desiccant air dryers contain two highly efficient polypropylene coalescer elements at inlet & outlet ports to absorb oil and solid air particles. Also included, one large desiccant bag specifically designed to absorb moisture and condensation from your compressed air system.



Distributed By:





www.modublast.com



Brochure #P1804