



SAFETY DATA SHEET

Section 1 – Identification

Product Identifier: ColorGard Satin Aluminum

Part Number: ALK

Recommended Use: Exhaust and High Temperature Coating

Restrictions on Use:

Manufacturer / Supplier:

Tech Line Coatings Industries, Inc
10840 CHAPMAN HWY UNIT A.
SEYMOUR, TN 37865
USA
Phone/Fax 1-865-773-0599
www.techlinecoatings.com

Keep out of reach of children.
Not recommended for use on Medical equipment.
Not recommended for use on Aviation equipment.

Emergency Phone: N. America +1-800-535-5053
Intl.+1-352-323-3500

Section 2 – Hazards Identification

Signal Word: Danger

Symbols:



Table with 2 columns: Hazard Statements and GHS Classification: Category. Lists various hazards like 'Flammable liquid and vapor' and 'Harmful in contact with skin' along with their corresponding GHS classifications.

Precautionary Statements:
Keep away from heat / sparks / open flames / hot surfaces. - No Smoking. Ground / bond container and receiving equipment.
Use explosion proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.
In case of fire use alcohol-resistant foam, dry chemical or carbon dioxide
Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Wear protective gloves / protective clothing (chemical proof). Wear eye protection and face protection. Wash hands, face and any exposed skin thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat drink or smoke when using this product. Do not breath fumes / mist / vapors / spray. Use only outdoors or in a well ventilated area.
If swallowed: immediately call a poison center / doctor for medical advice. Do NOT induce vomiting.

If on skin: wash with plenty of water. Call a poison center / doctor if you feel unwell or if irritation occurs. Immediately take off all contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center / doctor for medical advice.

If in eyes: Rinse cautiously in water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison control center / doctor.

If exposed or concerned: Get medical advise / attention, from a poison center / doctor.

Dispose of Contents / container in accordance with regulations in your area. See section 13 for additional information.

### **Section 3 – Composition / Information On Ingredients**

<b>Component Name</b>	<b>Common Name / Synonyms</b>	<b>CAS#</b>	<b>% of Weight</b>
PARACHLOROBENZOTRIFLUORIDE	PCBTF	98-56-6	< 25%
Aluminum Flake		7429-90-5	< 15%
Xylene		1330-20-7	< 10%
Mineral Spirits		64742-88-7	< 6%
Isobutyl Alcohol	Isobutanol	78-83-1	< 4%
Toluene		108-88-3	< 4%
Aromatic Hydrocarbon		64742-95-6	< 4%
Ethyl benzene		100-41-4	< 2%

Other ingredients are not hazardous based on OSHA standard Section 29 CFR 1910.1200

### **Section 4 – First Aid Measures**

#### **General Advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### **If inhaled**

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### **In case of skin contact**

Wash off with soap and plenty of water, and remove contaminated clothing shoes and leather goods. Consult a physician..

#### **In case of eye contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### **If swallowed**

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### **Section 5 – Fire Fighting Measures**

<b>Extinguishing Media:</b> Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.	<b>Special Fire Fighting Procedures:</b> Wear self contained breathing apparatus for fire fighting if necessary.
<b>Unusual Fire And Explosion Hazards:</b> Hazardous decomposition products formed under extreme fire conditions. - Carbon and other oxides. Vapors are heavier than air and may travel to a source of ignition and flash back.	<b>Additional Information:</b> Use water spray to cool unopened containers.

### **Section 6 – Accidental Release Measures**

#### **Methods for Containment and Clean Up**

- Soak up with inert absorbent material.
- Keep in suitable, marked and closed containers for disposal.

- Use spark-proof tools and explosion-proof equipment.
- Remove sources of ignition.
- Warn other workers of spill.
- Wear protective equipment
  - NIOSH Approved Respirator
  - Gloves
  - Safety Glasses
- Do not allow material to be released into the environment.

Additional Information:

- See Section 7 for safe handling information.
- See Section 8 for PPE information
- See Section 13 for disposal information

**Section 7 – Handling And Storage**

**Handling:**

Do not breathe vapors or mists from spraying. Avoid contact with skin and eyes. Use with adequate ventilation to maintain exposure levels below established exposure limits. Wear personal protective equipment. If required wear an appropriate NIOSH approved respirator with paint prefilter. Use explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

**Storage:**

Store in area suitable for flammable liquids. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition.

**Section 8 – Exposure Controls And Personal Protection**

Component	ACGIH TLV	OSHA PEL	NIOSH REL
PCBTF	Not Established	Not Established	Not Established
Aluminum Flake	15 MG/M3	10 MG/M3 TLV	No data available
Xylene	TLV: 100 ppm TWA: 150 ppm	TWA: 100 ppm	100 ppm 10 hour shift 200 ppm 10 minutes
Mineral Spirits	100 ppm	100 ppm	No data available
Isobutyl Alcohol	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
Toluene	TWA: 50 ppm	TWA: 300 ppm	STEL: 150 ppm TWA: 100 ppm
Aromatic Hydrocarbon	100 ppm	100 ppm	No data available
Ethyl benzene	TLV: 100 ppm TWA: 125 ppm	TWA: 100 ppm	TWA: 100 ppm

**Engineering Controls:**

Exhaust ventilation.  
Showers  
Eyewash stations  
Use in a well-ventilated area.

**Respiratory Protection:**

Use NIOSH approved respirator if TWA/TLV limits are exceeded

**Protective Gloves:**

CHEMICAL RESISTANT

**Eye Protection:**

SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES

**Other Protective Equipment:**

WEAR PROTECTIVE CLOTHING, CHEMICAL RESISTANT OR OTHER PROTECTIVE OUTERWEAR, AVOID CONTACT WITH SKIN OR EYES

**Ventilation:**

Local Exhaust: Use To Maintain Below TWA Limits

**Mechanical:**

Use Non-Sparking Equipment

**Work / Hygienic Practices:**

wash thoroughly after handling product and before eating, drinking or smoking

## Section 9 – Physical And Chemical Properties

Form :	liquid
Color :	Silver gray
Odor :	Mixture of Solvents
Odor Threshold:	Not Established
pH :	No data available
Melting point/range :	No data available
Initial boiling point :	> 150° F.
Flash point :	> 94° F.
Evaporation Rate:	No data available on mixture
Upper/lower flammability or explosive limits:	No data available on mixture
Vapor pressure	No data available on mixture
Vapor density	> 1 - (air =1)
Relative density	No data available on mixture
Solubility(ies)	No data available on mixture
Partition coefficient: n-octanol/water	No data available on mixture
Auto-ignition temperature	No data available on mixture
Decomposition temperature	No data available on mixture
Viscosity	< 19 centistokes at 72° F.
Total VOC	< 380 g/l

## Section 10 – Stability And Reactivity

<b>Stability:</b>	STABLE
<b>Possibility of hazardous reactions:</b>	Hazardous Polymerization: Will not occur.
<b>Conditions to avoid:</b>	Avoid storage of open containers at elevated temperatures. Heat, flames and sparks, direct sunlight.
<b>Incompatible Materials:</b>	Oxidizing material can cause a reaction.
<b>Hazardous Decomposition Products:</b>	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silicon dioxide. Carbon oxides. Metal oxides. Formaldehyde.

## Section 11 – Toxicological Information

### Potential Health Effects

Inhalation	Harmful if inhaled.
Ingestion	May be fatal if swallowed and enters airways
Skin	Harmful in contact with skin. Causes skin irritation.
Eyes	Causes Serious Eye Damage

### Acute Toxicity

PCBTF	Oral LD50	rat: LD50 = > 6700 mg/kg
	Inhalation LC50	rat: LC50 = > 4470 ppm/4H

Aluminum Flake	Dermal LD50	rabbit: LD50 = > 2700 mg/kg	
		No data available	
		No data available	
		No data available	
Xylene	Oral LD50	mouse: LD50 = 2119 mg/kg rat: LD50 = 4300 mg/kg	
	Inhalation LC50	rat: LC50 = 5000 ppm/4H	
Mineral Spirits	Dermal LD50	rabbit: LD50 = >1700 mg/kg	
	Oral LD50	rat: LD50 = > 5000 mg/kg	
	Inhalation LC50	rat: LC50 = > 5500 ppm/4H	
Isobutyl Alcohol	Dermal LD50	rabbit: LD50 = > 3000 mg/kg	
	Oral LD50	LD50 Oral - rat - 2,460 mg/kg LD50 Oral - rat - 2,500 - 6,400 mg/kg	
	Inhalation LC50	LC50 Inhalation - rat - 4 h - 8000 ppm	
	Dermal LD50	LD50 Dermal - rabbit - 3,400 mg/kg LD50 Dermal - rabbit - 4,240 mg/kg	
Other information on acute toxicity		LD50 Intraperitoneal - mouse - 544 mg/kg LD50 Intravenous - mouse - 417 mg/kg LD50 Intraperitoneal - rabbit - 323 mg/kg LD50 Intraperitoneal - guinea pig - 1,201 mg/kg LD50 Intraperitoneal - Hamster - 1,401 mg/kg	
	Toluene	Oral LD50	LD50 Oral - rat - > 5,580 mg/kg
		Inhalation LC50	LC50 Inhalation - rat - 4 h - 12,500 - 28,800 mg/m3
	Aromatic Hydrocarbon	Dermal LD50	LD50 Dermal - rabbit - 12,196 mg/kg
		Oral LD50	Source 1 - LD50 5 ppm Source 2 - 29003200mg/kg (rat), 8400mg/kg (rat)
Inhalation LC50		Source 1 - LD50 99 ppm Source 2 - approx. 2900ppm (rat)	
Ethyl benzene	Dermal LD50	Source 1 - LD50 3.16 ppm Source 2 - >3160mg/kg (rabbit)	
	Oral LD50	No data available	
	Inhalation LC50	No data available	
	Dermal LD50	LD50 Dermal - rabbit - 15,433 mg/kg	

### Skin Corrosion/Irritation

PCBTF

No data available

Xylene

Draize test, rabbit, skin: 100% Moderate;

Draize test, rabbit, skin: 500 mg/24H Moderate;

Isobutyl Alcohol

Skin - guinea pig - Mild skin irritation

Toluene

Skin - rabbit - Skin irritation - 24 h

### **Serious Eye Damage/Eye Irritation**

Isobutyl Alcohol

Eyes - rabbit - Remarks: Moderate eye irritation

### **Respiratory Or Skin Sensitization**

Isobutyl Alcohol

Dermatitis

### **Germ Cell Mutagenicity**

Toluene

Genotoxicity in vitro - rat - Liver

DNA damage

### **Carcinogenicity**

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Ethylbenzene)  
3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene, Xylene)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

This product contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Isobutyl Alcohol

Carcinogenicity - rat - Oral

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Skin and Appendages: Other: Tumors. Leukaemia

Carcinogenicity - rat - Subcutaneous

Tumorigenic: Carcinogenic by RTECS criteria. Gastrointestinal: Tumors. Liver: Tumors.

### **Reproductive Toxicity**

Toluene

Reproductive toxicity - rat - Inhalation

Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).

Experiments have shown reproductive toxicity effects in male and female laboratory animals.

Developmental Toxicity - rat - Oral

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Damage to fetus possible

Suspected human reproductive toxicant

### **Specific Target Organ Toxicity Single Exposure**

Isobutyl Alcohol

Inhalation - May cause respiratory irritation.

May cause drowsiness or dizziness.

Toluene

No data available

Ethylbenzene

No data available

### **Specific Target Organ Toxicity Repeated Or Prolonged Exposure**

No data available

### **Aspiration Hazard**

Aspiration into the lungs can cause fatal chemical pneumonitis.

**Further information:**

Fillers used in this product are the result of high temperature calcination of the component substances. Due to their unique crystalline structure the properties of this finished fillers do not necessarily reflect the properties of the component metals or oxides.

**Section 12 – Ecological Information****General Comments:**

Do not allow material to be released into the environment without proper governmental permits

**Environmental Toxicity:**

PCBTF		
	Toxicity to fish	No data available
	Toxicity to daphnia and other aquatic invertebrates	No data available
Aluminum Flake		
	Toxicity to fish	No data available
	Toxicity to daphnia and other aquatic invertebrates	No data available
Xylene		
	Toxicity to fish	Rainbow trout: LC50 = 13.5 mg/L; 96 Hr; Unspecified Goldfish: LD50 = 13 mg/L; 24 Hr; Unspecified Fathead Minnow: LC50 = 46 mg/L; 1 Hr
	Toxicity to daphnia and other aquatic invertebrates	No data available
Mineral Spirits		
	Toxicity to fish	No data available
	Toxicity to daphnia and other aquatic invertebrates	No data available
Isobutyl Alcohol		
	Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) – 1.220 mg/l - 96 h
	Toxicity to daphnia and other aquatic invertebrates	No Data Available
	Toxicity to algae	No Data Available
Toluene		
	Toxicity to fish	LC50 - Lepomis macrochirus (Bluegill) - 74.00 - 340.00 mg/l - 96 h LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d LOEC - Pimephales promelas (fathead minnow) - 8.04 mg/l - 7 d
	Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h
	Toxicity to algae	EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h
Aromatic Hydrocarbon		
	Toxicity to fish	LC50 (Fish, 96hr) 41 & 45mg/litre (Pimephelas promelas),

	2.34mg/litre (Oncorhynchus mykiss)
Toxicity to daphnia and other aquatic invertebrates	EC50 (Crustacea, 48hr) 0.95mg/litre (Daphnia magna)
Toxicity to algae	EC50 (Algae) <1 & 2.5mg/litre (Skeletonema costatum)
Ethylbenzene	
Toxicity to fish	LC50 - Cyprinodon variegatus (sheepshead minnow) - 88.00 mg/l - 96 h LC50 - Lepomis macrochirus (Bluegill) - 80.00 mg/l - 96 h NOEC - Cyprinodon variegatus (sheepshead minnow) - 88 mg/l - 96 h LC50 - Oncorhynchus mykiss (rainbow trout) - 4.2 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 2.90 mg/l - 48 h

**Section 13 – Disposal Considerations**

---

**Waste Disposal Method:**

**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? Yes

Characteristic Waste:

Ignitable: D001

TCLP: D018

State or local laws may impose additional regulatory requirements regarding disposal.

**Contaminated Packaging**

Dispose of as unused product.

**Section 14 – Transportation Information**

---

**Hazardous for Shipping:** Yes

**Based on 49 CFR, IATA and IMDG:**

**UN Number:** UN1263

**UN Proper Shipping Name:** Paint

**Hazard Class:** 3

**Packing Group:** III

**Labels:** Flammable Liquid

**Placards:** Flammable Liquid

**Section 15 – Regulations**

---

**TSCA (Toxic Substances Control Act) Regulations, 40 CFR 710:** All hazardous ingredients are on the TSCA Chemical Substance Inventory.

Component	%	CAS Number	SARA 313	SARA 302	New Jersey RTK List	Pennsylvania RTK List	Massachusetts RTK List	California Prop 65 list
PCBTF	< 25%	98-56-6	No	No	Yes	Yes	No	No
Aluminum Flake	< 15%	7429-90-5	Yes	Yes	No	No	No	No
Xylene	< 10%	1330-20-7	Yes	Yes	Yes	Yes	Yes	No
Dimethyl, diphenyl, methyl, phenyl silicone resin	< 15%	28630-33-3	No	No	Yes	Yes	No	No



Mineral Spirits	< 6%	64742-88-7	Yes	N/E	N/E	N/E	N/E	N/E
Isobutyl Alcohol	< 4%	78-83-1	No	No	Yes	Yes	Yes	No
Toluene	< 4%	108-88-3	Yes	Yes	Yes	Yes	Yes	Yes
Aromatic Hydrocarbon	< 4%	64742-95-6	N/E	N/E	N/E	N/E	N/E	N/E
Ethyl benzene	< 2%	100-41-4	Yes	No	Yes	Yes	Yes	Yes

\* Please note that these were random sample analyses and content may vary from batch to batch.

**SARA 311 / 312 Hazards:** Flammable Hazard ,Acute Health Hazard, Chronic Health Hazard

**Section 16 – Other Information**

---

**Date Prepared:** 05/27/2014

**Date Updated:** 1/26/2017

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Tech Line Coatings Industries, Inc., knowledge or obtained from sources believed by Tech Line Coatings Industries, Inc. to be accurate but does not purport to be all inclusive, and Tech Line Coatings Industries, Inc., does not assume any legal responsibility for use or reliance upon same. Before using any chemical, read its label, instructions and safety data sheet.